

ONDA


Porcelain Wall Tile

Available in 2.4” x 10” x 5/16”






ONDA WHITE
2.4” X 10” X 5/16”
IFS2.4X10OW



ONDA MOTHER OF PEARL
2.4” X 10” X 5/16”
IFS2.4X10OMOP



ONDA COBALT
2.4” X 10” X 5/16”
IFS2.4X10OC



ONDA EMERALD
2.4” X 10” X 5/16”
IFS2.4X10OE

TECHNICAL SPECIFICATIONS

Water Absorption 0.5% < E ≤ 3%	**Modulus of Rupture** ≥30 N/mm²	**Color Shade Variation** V1	**Chemical Resistance** HB / LB	**Stain Resistance** Resistant
Breaking Strength >1100 N	**Thermal Shock Resistance** Resistant	**MOHS** Not Provided	**Recommended Grout Joint** 1/16”	**Frost Resistance** Resistant

REACTIVE GLAZE — COLOR & FINISH VARIATION

These tiles feature a reactive glaze that develops natural variations in color, shading and surface effects during firing. The glaze responds differently across raised and recessed areas, creating a distinctive finish. Variations occur between individual tiles and production runs. Samples illustrate the general character of the collection; actual orders may differ in color and finish from the samples shown.





Due to the natural variation of fired porcelain, the colors and sizes shown may vary slightly.
Please verify with actual product samples before installation.